



Sheet 09 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

Description

BACKGROUND OF THE INVENTION

The present invention relates to a radio transmitter receiver system, and more particularly to an emergency radio transmitter receiver system which creates an Emergency Vehicle Environment (EVE) for unobstructing the path of emergency vehicles resulting in increased response times and safety.

The current system for clearing the path of emergency vehicles is the combined use of sirens and flashers. The sirens are not heard until the emergency vehicle is very close, if at all; The flashers are not seen by drivers going the same direction until rear view mirrors are checked, if at all. The present invention transduces the emergency vehicle's siren to a strobe light already in all of the drivers' lines of sight.

The problems with the said current system are illustrated with an aerial view in FIG. 1. (All non-emergency vehicles are collectively called cars even though this group includes trucks, buses, RVs, etc.) The emergency vehicle 1 has relatively clearer passage on the more dangerous, opposite side of the road since

Inventor: Custs J. Martin Date: 03,15,02

The above confidential information is Witnessed and Understood:

Date: 03 1 15 1 02



Sheet 10 of 21

Inventor:	Curtis Jude Martin		
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA		
Title of Invention:	E.V.E. Emergency Vehicle Environment		

the oncoming cars 2 can see the flashers. The cars 3 in the same lane and closer have no direct visual warning and are slower to pull over, due to having to hear the siren and then see the flashers in rear view mirrors. The cars 4 are stopped at the intersection's red traffic light 6 and are obstructing the path usurping time. The cars 5 are the most dangerous since they are entering the intersection with a green traffic light 6 and are not aware of the sirens and flashers.

1



Sheet 11 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

SUMMARY OF THE INVENTION

The solution that EVE affords is illustrated with an aerial view in FIG. 2. The emergency vehicle 7 has clear passage on either side of the road since all cars have visual confirmation of an emergency vehicle's approach from their miniature mobile blinking receivers in their car's interiors and/or the immobile traffic light's blinking blue receiver 11. None of the cars has to rely on direct sensory perception of the emergency vehicle's sirens and flashers. The cars 8 that were stopped at the intersection's red traffic light are now pulled over. The cars 9 previously the most dangerous are now the least dangerous. Cars 10 that need not be inconvenienced, are not.

Accordingly, it is an object of the present invention to provide an emergency transmitter which is relatively inexpensive to manufacture, durable in structure, requires no maintenance if the vehicle's power supply is used, requires little maintenance if the vehicle's power supply is not used, quick and easy to install, efficient in operation and operates automatically if/when desired.

Another object of the present invention is to provide car

Inventor: Outre J. Martin	Date: <u>03</u> 1 <u>/5</u> 1 <u>0</u> 2
The above confidential information is Witnessed and Unders	
Patricia M. Jarrison	Date: <u>03115102</u>
Chester D. Minten	Date: 03 1 15 1 02



Sheet 12 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

receivers that are extremely inexpensive to manufacture, durable in structure, requires no maintenance, extremely quick and easy to install, efficient in operation and operates automatically.

Another object of the present invention is to provide blue traffic light receivers that are inexpensive to adapt to unused existing traffic lights, relatively inexpensive to add to newly manufactured traffic lights, durable in structure, require little maintenance, efficient in operation and operate automatically.

Another object of the present invention is to provide an EVE that can increase response times for ambulances to victims and then to hospitals.

Another object of the present invention is to provide an EVE that can increase response times for fire trucks to victims and reduce property damage.

Another object of the present invention is to provide an EVE that can increase response times to crime victims and reduce property loss.

Inventor: Outre J. Maitin Date: 03,15,02

The above confidential information is Witnessed and Understood:

hester D. Martin Date: 03/15/02



Sheet <u>13</u> of <u>21</u>

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment
that can inc	ect of the present invention is to provide an EVE crease safety at dangerous school bus stops using a asmission range.
	ect of the present invention is to provide an EVE duce emergency vehicle caused accidents, injuries and
that can red	ect of the present invention is to provide an EVE duce accidents in high-speed pursuits (the only car be the suspect).
that can red	ect of the present invention is to provide an EVE duce railroad crossing train and car/pedestrian especially where crossing gates are not erected.
that can ena	ct of the present invention is to provide an EVE ble unmarked law enforcement, secret service and essions clear passage.
that can ena	ct of the present invention is to provide an EVE . ble an immobilized area from a police helicopter for al Guard, etc.
Inventor: Qui	The f. Martin Date: 03, 15, 02
	al information is Witnessed and Understood:
Latricia	M. (Jahreson) Date: 03/15/02
1 60-TO- 1) hot to



Sheet 14 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

Another object of the present invention is to provide an EVE that can enable helicopter ambulances to clear a landing area.

Another object of the present invention is to provide an EVE that can enable airport air traffic control to clear freeways for emergency landings.

Another object of the present invention is to provide an EVE that can enable citywide car immobilization from a local radio station such as for the touch down of a tornado.

Another object of the present invention is to provide an EVE which can enable the deaf, hard of hearing and drivers with windows up, air-conditioning on high with radios on, to safely pull over their cars.

The current system for clearing the path of emergency vehicles with the use of sirens and flashers is inferior to the current system with the addition of the present invention. Other objects, features and advantages of the present invention will become apparent from the following description when taken in conjunction with the accompanying drawings.

Inventor: <u>Cutto f. Mastru</u>

Date: <u>03, 15, 02</u>

The above confidential information is Witnessed and Understood:

Date: <u>03, 15, 02</u>

Date: <u>03, 15, 02</u>

__ Date: <u>03</u> / 15 / 62



Inventor: Curtis Jude Martin	
Address: 1675 East Main Street - Kent, Ohio 44240-58	18 - USA
Title of Invention: E.V.E. Emergency Vehicle Environment	
_	
BRIEF DESCRIPTION OF THE DRAWINGS	
FIG. 1 is an illustrated aerial view of the relative	
ineffectiveness of an emergency vehicle's ability to warn	
passenger vehicles of its approach;	
FIG. 2 is an illustrated aerial view of the effectiveness	of an
emergency vehicle's ability to warn passenger vehicles of	its
approach employing EVE;	
FIG. 3 is an applied and illustrated view of EVE consisti	ng of
the emergency vehicle's external or internal transmitter	
communicating with the passenger vehicle's mounted mobile	
receiver and the immobile blinking blue traffic light receiver	eiver;
FIG. 4 is an illustration and a block diagram of the major	r
components of the transmitter according to the present	
invention;	
FIG. 5 is an enlarged, perspective view of the transmitter	r ,
according to the present invention;	
FIG. 6 is an applied view with an illustration and a block	k
	٦
nventor: Outlie J. Maita Date: 03,	<i></i>
nventor:	13102
The above confidential information is Witnessed and Understood:	
Patricia M. (Jarrison) Date: 031	15102
Chester D. Martin Date: 03/1	



Sheet 16 of 21

I	
Inventor:	Curtis Jude Martin
Address: Title of Invention:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
	E.V.E. Emergency Vehicle Environment
Γ	
diagram of t	the major components of the mounted mobile receiver
according to	o the present invention;
_	
riG. / is ar	n enlarged, perspective view of the mobile receiver
according to	the present invention;
FIG. 8 is an	n illustration with a block diagram of the major
	- · · · · · · · · · · · · · · · · · · ·
components of	of the factory installed mobile receiver according to
the present	invention; and
FIG. 9 is ar	n illustration of immobile receiver housings
according to	the present invention.
	•
1	-1 1
nventor:	tre J. Mustin Date: 03, 15, 00
invertion	Date: 0 3 10 6
The above confidenti	al information is Witnessed and Understood:
Fatricia	M. Garrison Date: 031 15102
Cho To NO	h
rusce-1).	Thankin Date: 03 115102



Sheet 17 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 3, an Emergency Vehicle Environment (EVE) is created with the use of three devices named a transmitter, a mobile receiver and an immobile receiver. The transmitter is adhered externally to the emergency vehicle in proximity to the vehicle's siren, whistle, etc, or internally on the dashboard. The mobile receiver is adhered to the dashboard or windshield on the passenger car. The immobile receiver is installed inside the 4-way blue traffic light. When the emergency vehicle actuates its siren the transmitter automatically transmits a signal on a preset carrier frequency already designated for emergency communications with a factory preset signal range that does not carry any appreciable distance beyond the requirements of the emergency vehicle's necessitation. The accelerometer increases the signal's range the faster the emergency vehicle is moving and decreases the signal range the slower the emergency vehicle is moving. The mobile receiver then receives the signal and actuates its strobe light that the driver of the car then unmistakably sees on the dashboard, windshield or instrument panel. The immobile receiver situated at historically dangerous intersections, crowded venues, etc., also receives the signal and actuates its blinking blue traffic light for drivers that do

Inventor:	auto f	. Mactr	Date:	03,15,0	2
The above of	confidential informati	ion is Witnessed and Und	erstood:		
Fatr.	icia, M.	James	Date:	03 1 (5 100	_
Chert	Ter 1 m	<i>7</i> I		<u>Λ</u> 3 1/5 1 Ø 3	

_1



Sheet 18 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

not yet have mobile receivers, inoperative mobile receivers, pedestrian railroad crossings, etc. The drivers then proceed to safely pull their cars over and out of the way of the emergency vehicle.

Referring to FIG. 4, this will be understood by those skilled in the art that the transmitter's printed circuit board of the transmitter is of conventional construction and is divulged in prior art. With the transmitter mounted externally, the on-auto-off switch is switched to the auto position only. The emergency vehicle's siren is then actuated by the emergency vehicle's operator, as it normally would be. The siren actuates the condenser microphone. The condenser microphone actuates the transmitter. The accelerometer adjusts the signals range. The transmitter transmits the signal via the internal directional antenna. The LED is for indicating a low battery power supply.

Referring to FIG. 5, the on-auto-off switch 20 is switched to the auto position when the transmitter is adhered with a peel and stick perimeter 16 externally to the emergency vehicle enabling the transmitter to automatically actuate when the siren is actuated. The condenser microphone 18 is actuated by the actuation of the siren, unless it is overridden by hardwiring

Inventor:	Custra	J. Mrsetta	Date: _	03,15,	02
		tion is Witnessed and Under			
Yal	icia M	. Januaron	Date: _	031151	02
Chest	Ter D. M	and		13 115 1	



Sheet 19 of 21

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment

from the vehicle's siren switch at input port 19. The condenser microphone 18 then actuates the transmitter mounted within the upper cover shell 14. The transmitter transmits the signal forward via the internal directional antenna 12. The accelerometer 22 automatically adjusts the signal's range when the on/off switch 23 is on. The accelerometer extension port is 21. The LED 13 is for indicating a low power supply. The battery lid cover 15 on the battery chamber is for accessing batteries. The external power supply input port 17 is for connecting a power cord to the vehicle's power supply, overriding the batteries as a power source.

Mounting the transmitter wholly externally affords extremely quick and easy installation, but requires battery replacements 15. Mounting the transmitter internally, eliminates battery maintenance and enables manual operation of the on-auto-off switch 20, but requires installation. Another option is to mount the transmitter externally with the power cord connecting the external power supply input port 17, to the vehicle's power supply via the power feeding the flashers and/or siren. The best mode is internally.

Referring to FIG. 6, this will be understood by those skilled in

Inventor: Cutte J. Month	Date: <u>03 15 02</u>
The above confidential information is Witnessed and Underst	tood:
Fatricia M. Garrison	Date: <u>03 5 02</u>
Chester D. Martin	Date: 03 115 102



Sheet 20 of 21

Inventor:	Curtis Jude Martin		
Address:	1675 East Main Street - Kent, Ohio 44240-5818 - USA		
Title of Invention:	E.V.E. Emergency Vehicle Environment		

the art that the receiver's printed circuit board is of conventional construction and is divulged in prior art. With the mobile receiver, the internal omni-directional antenna receives the transmitter's signal that actuates the receiver. The receiver actuates the strobe light that alerts the car's driver to pull over. When the test switch button is depressed, if the strobe light does not actuate the battery is low or the unit needs replacing.

Referring to FIG. 7, the mounted mobile receiver 24 is adhered with a peel and stick rectangular pad 26 (backside) to the passenger car's dashboard or windshield. Upon receipt of the transmitter's dedicated signal the strobe light 25 is actuated. The test switch button 27 is to make sure the unit is functioning properly.

Referring to FIG. 8, the installed mobile receiver is the mounted mobile receiver installed at the factory as original equipment and is hidden within the dashboard. The bottom cover plate, antennas, test switch and battery terminal connectors are omitted. An antenna cable conjoins the car's radio antenna. The receiver's power supply conjoins the car radio power supply. The strobe light is mounted in the vehicle's instrument panel with

Inventor: Outra J. Wasten	Date: <u>03</u> 1 <u>/5</u> 1_02
The above confidential information is Witnessed and U	
Patricio M. garrese	57) Date: 03 1 15 1 6 2
Checter D. Marti	Date: 03 1/5 1 82



Sheet $\underline{21}$ of $\underline{21}$

Inventor:	Curtis Jude Martin
Address:	1675 East Main Street ~ Kent, Ohio 44240-5818 - USA
Title of Invention:	E.V.E. Emergency Vehicle Environment
wire cable installed.	extending to the receiver. The best mode is factory
Referring t	o FIG. 9, the immobile receivers' housings can take
the form of	conventional traffic lights 29 and have blinking
blue lights	28 or use the round beacon form 31 and have rotating
blue lights	or blue strobe lights 30. The immobile receivers in
either hous	ing can be added to a red-yellow-green traffic light,
blinking re	d/yellow, 4-way, 2-way, stand-alone, post, pole, etc.
It is to be	understood that the drawings are designed for
purpose of	illustration only, and are not intended as a
definition	of the limits and scope of the invention disclosed.
	END
1111111111	
1111111111	
11111111111	***************************************
1111111111	
1111111111	
1111111111	
1111111111	
1111111111	
Inventor: Our	tra J. Minster Date: 03, 15, 02
The above confident	tial information is Witnessed and Understood:
Latricie	Matter Date: 03 1 15 1 00
Kester D	MATEL 102